



## Pigtail datasheet

PN / Parameter	UFL-RF	UFL-SMM	MMCX-SMM	MMCX-MMCX-25	MMCX-RSM90
Cable type	RG178	RG178	RG178	RG316	RG316
Length	0,25m	0,25m	0,25m	0,25m	0,25m
Impedance	50 Ohm	50 Ohm	50 Ohm	50 Ohm	50 Ohm
Max. attenuation	1,5dB	1,5dB	1,5dB	1,5dB	1,5dB
Connector	U.FL male	U.FL male	MMCX male	MMCX male	MMCX male
Connector	RSMA female	SMA male 90°	SMA male 90°	MMCX male	RSMA male 90°

PN / Parameter	RM-RM	UFL-NM90	UFL-NF	UFL-NM	MMCX-NM
Cable type	RG316	RG178	RG178	RG178	RG316
Length	0,25m	0,25m	0,25m	0,25m	0,25m
Impedance	50 Ohm	50 Ohm	50 Ohm	50 Ohm	50 Ohm
Max. attenuation	1,5dB	1,5dB	1,5dB	1,5dB	1,5dB
Connector	RSMA male	U.FL male	U.FL male	U.FL male	MMCX male
Connector	RSMA male	N male 90°	N female	N male	N male

PN / Parameter	MMCXS-RSF	MMCX-NF	MMCX-RSF	UFL-RSM90	MMCX-NM90
Cable type	RG316	RG316	RG316	RG178	RG316
Length	0,25m	0,25m	0,25m	0,25m	0,25m
Impedance	50 Ohm	50 Ohm	50 Ohm	50 Ohm	50 Ohm
Max. attenuation	1,5dB	1,5dB	1,5dB	1,5dB	1,5dB
Connector	MMCX male straight	MMCX male	MMCX male	U.FL male	MMCX male
Connector	RSMA female	N female	RSMA female	RSMA male 90°	N male 90°