

# CO-sinusUPS-400W

Pure sine wave inveter (400W)



## ■ Features:

- Easy user interface
- Compact size
- Low price



## ELECTRICAL SPECIFICATION

MODEL	CO-sinusUPS-400W
<b>OUTPUT</b>	
Rated Power	400W
Output voltage range (AC mode)	200-250VAC ( $\pm 7$ VAC)
Output voltage (Battery mode)	220VAC ( $\pm 10$ VAC)
Output frequency (Battery mode)	50Hz
Output waveform	Pure sine wave
Transfer time	< 10ms
<b>INPUT</b>	
Voltage Range	155 ÷ 264VAC ( $\pm 7$ VAC)
Input frequency	50Hz
<b>BATTERY</b>	
Charging current (max.)	6A
Type and capacity of battery	12V GEL / AGM / WET; 26-100Ah
<b>WORKING ENVIRONMENT</b>	
Working Temperature	0°C ÷ 40°C
Working Humidity	20 ÷ 90% RH non-condensing
Noise level	< 40dB (1m)
<b>OTHERS</b>	
Wire input	Electric plug - SCHUKO - H05VV-F AWG16 (3x0.75mm <sup>2</sup> ) – 1350mm
Wire output	Red – 820mm, black – 790mm; 8AWG (8mm <sup>2</sup> ); Ring terminal - M8
Dimensions	5.9 kg 246 x 205 x 104mm (L x W x H)
Weight and box dimension	6.3 kg; 305 x 265 x 180 mm (L x W x H)

EAN code



## MECHANICAL SPECIFICATION

