

Pan/Tilt Home Security Wi-Fi Camera

Tapo C200C



Person Detection Baby Crying Detection

Night Vision up to 40 ft

1080p Full HD









Highlight

Motion Detection and Tracking

Whenever a camera detects motion, it will automatically follow the subject, keeping it within the camera's field of view.





Features



Person Detection

Notifies you when a person is detected.



Night Vision up to 40 ft

Provides a visual distance of up to 40 ft in total darkness.



Two-Way Audio

Communicate in real time through a built-in microphone and speaker.



Baby Crying Detection

Notifies you when your baby cries.



Local microSD Storage[†]

Store up to 512 GB of video on a microSD card[†].



1080p Full High Definition

Provides greater sharpness and clarity.



Field of View

360° horizontal range.



Customizable Block Zones

Set customizable block zones to keep private areas from being monitored.



Cloud Storage Supported[‡]

Store videos by using cloud storage services.

[†]microSD card needs to be purchased separately. Actual storage capacity depends on the size of the microSD card used.

*Subscribe for cloud storage at https://www.tapo.com/tapocare/

For more information, please visit https://www.tapo.com/

All brands and product names are trademarks or registered trademarks of their respective holders. Specifications are subject to change without notice.

©2024 TP-Link



Specifications

Camera	Image Sensor	1/3" Progressive Scan CMOS Not Starlight Sensor
	Lens	Focal Length: 4 mm Aperture: F2.0 Field of View: 89.7° (Diagonal), 76.7° (Horizontal), 42.0° (Vertical)
	Night Vision	850 nm IR LED (40 ft / 12 m)
	Day/Night Switch	IR-Cut Filter with Auto-Switching
	Lighting	/
	Interface & Button	1× RESET Button 1× microSD Card Slot (Up to 512 GB)
	Hub Compatibility	/
Video & Audio	Maximum Resolution	1080P HD (1920 x 1080 px)
	Frame Rate	30 fps
	Digital Zoom	None
	Video Compression	H.264
	Live View	Yes
	Image Enhancement	3DNR WDR



Video & Audio	Audio Input & Output	Built-in Microphone and Speaker
	Audio Communication	Two-Way Audio with Noise Cancellation
	Siren Volume	88 dB (Level measured at 4-inch/10-cm distance)
Storage	Local Storage	microSD Card Slot on Camera (Up to 512 GB)
	Cloud Storage	Tapo Care Cloud Storage Services (Subscription required)
Detection & Notification	Sensor	/
	Al Detection	Motion Detection Person Detection Baby Crying Detection
	Activity Zones	Yes *Only works with Motion Detection.
	Output Notification	System Notification System Notification with Snapshot (Tapo Care Services)
Network	Network Connectivity	Connect via Wi-Fi
	Wireless Connectivity	IEEE 802.11b/g/n, 2.4 GHz Wi-Fi
	Transmission Rate	11b: 11 Mbps 11g: 54 Mbps 11n: 72.2 Mbps
	Protocol	TCP/IP, DHCP, ICMP, DNS, NTP, HTTPS, TCP, UDP
	Max. Distance Between Hub and Camera/Doorbell	/



Network	Ethernet Port	
	RTSP	Yes
	ONVIF	Yes
Security	Security	On-Device Machine Learning 128-bit AES Encryption with SSL/TLS WPA/WPA2-PSK
Power	Power Source	9V DC Power Adapter
	Input Voltage	100-240 V, 50/60 Hz
	Output Voltage	9 V, 0.6 A (DC Power)
	DC Power Connector Size	Inside Ø: 2.1 mm Outside Ø: 5.5 mm
	Power Cord Length	1.5 m
	Typical Power Consumption	1.3 W
	Maximum Power Consumption	3.5 W
General	Certifications	CE, UKCA, RCM
	Smart Integration	Google Assistant, Amazon Alexa
	Weather Resistance	
	System Requirements	Tapo App: iOS 11.0 or higher, Android 5.0 or higher



	Mounting Options	Tabletop Ceiling-Mounted
	Operating Temperature	0 °C ~ 40 °C (32 °F ~ 104 °F)
	Storage Temperature	-20 °C ~ 60 °C (-4 °F ~ 140 °F)
	Operating Humidity	10%~90% RH, Non-condensing
	Storage Humidity	5%~90% RH, Non-condensing
General	Charging Temperature	\
	Mounting Screw Size	at every least the second seco
	Dimensions	3.36 × 3.42 × 4.63 in (85.4 × 86.8 × 117.7 mm)
	Weight	6.7 oz / 190 g
	Package Contents	Tapo C200C Camera Power Adapter Quick Start Guide Mounting Anchors Mounting Screws Mounting Template