

Huawei OptiXstar EN8245X6s-8N Datasheet

Huawei intelligent XGS-PON and Wi-Fi 6 routing-type ONT

Overview

The Huawei OptiXstar EN8245X6s-8N is an XGS-PON and Wi-Fi 6 routing-type ONT. It uses the XGS-PON and Wi-Fi 6 technologies to implement ultra-broadband access, high performance and wide coverage for users. The high forwarding performance ensures the user experience of voice and data services, and provides customers with an ideal all-optical access solution and future-oriented service support capability.

It provides one 2.5GE port, three GE ports, two POTS ports, one USB port and 2.4GHz&5GHz Wi-Fi 6 function.

- Next generation Wi-Fi 6 technology
- Smart service
- Smart interconnection
- Smart O&M



Device Parameters

Operating temperature	0°C to +40°C	NNI	XGS-PON
Operating humidity	5% RH to 95% RH (non-condensing)	UNI	1x2.5GE+3xGE+2xPOTS+2.4 GHz/5GHz Wi-Fi 6+1USB
Power adapter input	100–240 V AC, 50/60 Hz	Optical connector	SC/APC
System power supply	12 V DC, 3 A	Indicators	Power/PON/LOS/LAN/2.5G LAN/TEL/USB/WLAN/WPS
Static power consumption	12.1 W	Dimensions	247.5mm x 216.5mm x 72mm (without pads)
Maximum power consumption	30 W	Weight	About 765 g
Antenna type	Internal antennas	Memory	128MB Flash, 512MB RAM

Interface Parameters

<p>XGS-PON port</p> <ul style="list-style-type: none"> • Class N1/N2/E1 • Receiver sensitivity: -28 dBm • Wavelengths: US 1260-1280 nm, DS 1575-1580 nm • Upstream and downlink rate: 9.953 Gbit/s upstream, 9.953 Gbit/s downstream • Wavelength blocking filter (WBF) • Flexible mapping between GEM Port and TCONT • SN/Password/SN+Password/Bi-directional authentication based on OMCI • Upstream and downstream FEC • SR-DBA and NSR-DBA 	<p>POTS port</p> <ul style="list-style-type: none"> • Maximum ringer equivalence number (REN): 4 • G.711A/μ, G.729a/b and G.722 encoding/decoding • T.30/T.38/G.711 fax mode • DTMF • Emergency calls (with the SIP protocol)
	<p>USB port</p> <ul style="list-style-type: none"> • USB2.0 • FTP-based network storage • File/Print sharing based on SAMBA • DLNA function
<p>WLAN</p> <ul style="list-style-type: none"> • IEEE 802.11 b/g/n/ax (2.4G) • IEEE 802.11 a/n/ac/ax (5G) • 4 × 4 MIMO (2.4G) • 4 × 4 MIMO (5G) • 2.4G&5G concurrent • Antenna gain: 2 dBi • Air interface rate: 1147 Mbit/s (2.4G), 4804 Mbit/s (5G) • 4096 QAM • 160MHz frequency bandwidth • OFDMA • UL/DL MU-MIMO • DCM • BSS Coloring • Beamforming 	<p>Ethernet port</p> <ul style="list-style-type: none"> • Ethernet port-based VLAN tags and tag removal • 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission • QinQ VLAN • Limit on the number of learned MAC addresses • MAC address learning • GE port supports auto-adaptive 10 Mbit/s, 100 Mbit/s or 1000 Mbit/s • 2.5GE port supports auto-adaptive 1000 Mbit/s or 2500 Mbit/s

- Band steering
- WPA3
- WMM/Multiple SSIDs/WPS


Product Function

Smart interconnection	Smart service	Smart O&M	Common O&M
<ul style="list-style-type: none"> • Smart Wi-Fi coverage • SIP/H.248 auto-negotiation • Any port any service • Parental control 	<ul style="list-style-type: none"> • Scheduled Wi-Fi shutdown • Smart Wi-Fi sharing: Portal/802.1x authentication; SoftGRE-based sharing • Association of one account with two POTS ports 	<ul style="list-style-type: none"> • IPTV video quality diagnosis • eMDI • Rogue ONT detection and isolation from the OLT • Call emulation, and circuit test and loop-line test • PPPoE/DHCP simulation testing • Neighboring AP scanning 	<ul style="list-style-type: none"> • OMCI/Web UI/TR069 • Variable-length OMCI messages • Dual-system software backup and rollback
Multicast	Security	Layer 3 features	Home network feature
<ul style="list-style-type: none"> • IGMP v2/v3 proxy/snooping • MLD v1/v2 snooping 	<ul style="list-style-type: none"> • SPI firewall • Filtering based on MAC/IP/URL addresses 	<ul style="list-style-type: none"> • PPPoE/Static IP/DHCP • NAT/NAPT • Port forwarding • ALG, UPnP • DDNS/DNS server/DNS client • IPv6/IPv4 dual stack, DS-Lite and IPv6 SPI • Static/Default routes • Multiple services on one WAN port 	<ul style="list-style-type: none"> • Visualized home network management • User-defined bandwidth allocation • Wi-Fi optimization & Wi-Fi roaming • Wi-Fi O&M
Power saving	QoS		
<ul style="list-style-type: none"> • Indicator power saving 	<ul style="list-style-type: none"> • Ethernet port rate limitation • 802.1p priority • SP/WRR/SP+WRR • Broadcast packet rate limitation 		

Copyright © Huawei Technologies Co., Ltd. 2022. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademarks and Permissions

 HUAWEI and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

Huawei Technologies Co., Ltd.

Address: Huawei Industrial Base Bantian,
Longgang Shenzhen 518129 People's
Republic of China

Website: <http://www.huawei.com>